



4100/4200 Spec. Comparison

4100
4200

Gas Models, Liquid Cooled

Model	4131	4227
Stock Code	3.95112	39.51200
Trademark Name	Ventrac	Ventrac
Power Unit:		
Engine Manufacturer	Briggs & Stratton Vanguard	Kawasaki Gas
Engine Model	543477-0144	FD750D
Horsepower	31	27
Configuration	2-cylinder	2-cylinder
Cooling	Air-Cooled	Liquid-cooled
CARB Compliant Engine	Yes	Yes
EPA Compliant Engine	Yes	Yes
Air Filtration	Donaldson 2-stage	
Spin-on Oil Filter	Yes	Yes
Electrical System	50 amp	20 amp
Starter	Electric	Electric
Battery Capacity	12V/450CCA	12V/450CCA
Transmission:		
Drive	AWD	AWD
High/Low Shift from Seat	Std	Std
Transmission	Hydrostatic	Hydrostatic
Forward/Reverse Speed, High Range	0-10 MPH (0-16.1 KPH) Infinitely variable	0-10 MPH (0-16.1 KPH) Infinitely variable
Forward/Reverse Speed, Low Range	0-5.2 MPH (0-8.4 KPH) Infinitely variable	0-5.2 MPH (0-8.4 KPH) Infinitely Variable
Brakes	Hydro-Dynamic	Hydro-Dynamic
Spin-on Oil Filter-suction	25 microns	25 microns
Spin-on Oil Filter-pressure	10 microns	10 microns
Controls/Instrumentation:		
Steering	Power	Power
Blade Engage/PTO	Electric w/Brake	Electric w/Brake
Throttle Control/Choke	Std w/Manual Choke	Std w/Manual Choke
Operator Control *	S.D.L.A. / Std *	S.D.L.A. / Std *
Speed Control	Easy Shift	Easy Shift
Gauges:Temp/Hour/Tach	Std	Std
Park Brake/Emergency	16 in ² brake surface (103 cm ²)	16 in ² brake surface (103 cm ²)

Model	4131	4227
Other Features:		
Center Articulated Tractor	Yes	Yes
Turning Radius (appx)	43 Inches (109 cm)	43 Inches (109 cm)
Drive Tires	22 x 12-8 HD Field Trax (56x31x20 cm)	22 x 12-8 HD Field Trax (56x31x20 cm)
Optional Tires	21 x 11-8 Bar (53x28x20 cm)	21 x 11-8 Bar (53x28x20 cm)
	22 X 11-10 Turf Master (56x28x25 cm)	22 X 11-10 Turf Master (56x28x25 cm)
Seat-Spring Ride	Std	Std
Front Fenders	Optional	Std
Headlights, Halogen	Std	Std
Fuel Tank Capacity	6.0 gal. (22.7L)	6.0 gal. (22.7L)
Visual Fuel Gauge Slot	Std	Std
Counter Weights (168 Lbs/76.2 kgs)	Optional	Std
Weight Transfer System	Optional	Adjustable
Racor Fuel Water Separator	Optional	Opt
Foot Rest	Optional	Std
Ventrac Mount System	Std	Std
ROPS Roll Bar	Optional	Std
Weight (appx)	1290 lbs (585 kgs)	1460 lbs (662 kgs)

* S.D.L.A.- Speed, Direction, Lift, AUX. Control / single hand operation

Specifications Subject to Change Without Notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667

330.683.0075 • 1.866.VENTRAC (836.8722)

Fax: 330.683.0000

www.ventrac.com • info@ventrac.com



4100/4200 Spec. Comparison

4200

Diesel Models

Model	4226D	4231TD
Stock Code	39.51204	39.51205
Trademark Name	Ventrac	Ventrac
Power Unit:		
Engine Model	DM950D	DM950DT
Horsepower	26.5	31
Configuration	3-cylinder	3-cylinder
Cooling	Liquid-cooled	Liquid-cooled
CARB Compliant Engine	Yes	Yes
EPA Compliant Engine	Yes	Yes
Spin-on Oil Filter	Yes	Yes
Electrical System	40 amp	40 amp
Starter	Electric	Electric
Battery Capacity	12V/450CCA	12V/450CCA
Transmission:		
Drive	AWD	AWD
High/Low Shift from Seat	Std	Std
Transmission	Hydrostatic	Hydrostatic
Forward/Reverse Speed, High Range	0-10 MPH (0-16.1 KPH) Infinitely variable	0-10 MPH (0-16.1 KPH) Infinitely variable
Forward/Reverse Speed, Low Range	0-5.2 MPH (0-8.4 KPH) Infinitely Variable	0-5.2 MPH (0-8.4 KPH) Infinitely variable
Brakes	Hydro-Dynamic	Hydro-Dynamic
Spin-on Oil Filter-suction	25 microns	25 microns
Spin-on Oil Filter-pressure	10 microns	10 microns
Controls/Instrumentation:		
Steering	Power	Power
Blade Engage/PTO	Electric w/Brake	Electric w/Brake
Throttle Control/Choke	Std w/Glow Plug	Std w/ Glow Plug
Operator Control *	S.D.L.A. / Std *	S.D.L.A. / Std *
Speed Control	Easy Shift	Easy Shift
Gauges: Temp/Hour/Tach	Std	Std
Park Brake/Emergency	16 in ² brake surface (103 cm ²)	16 in ² brake surface (103 cm ²)

Model	4226D	4231TD
Other Features:		
Center Articulated Tractor	Yes	Yes
Turning Radius	43 Inches (109 cm)	43 Inches (109 cm)
Drive Tires	22 x 12-8 HD Field Trax (56x31x20 cm)	22 x 12-8 HD Field Trax (56x31x20 cm)
Optional Tires	21 x 11-8 Bar (53x28x20 cm)	21 x 11-8 Bar (53x28x20 cm)
	22 X 11-10 Turf Master (56x28x25 cm)	22 X 11-10 Turf Master (56x28x25 cm)
Seat-Spring Ride	Std	Std
Front Fenders	Std	Std
Headlights, Halogen	Std	Std
Fuel Tank Capacity	7.25 gal. (27 lt)	7.25 gal. (27 lt)
Visual Fuel Gauge Slot	Std	Std
Counter Weights	180 lbs.	180 lbs.
Weight Transfer System	Adjustable	Adjustable
Racor Fuel Water Separator	Std	Std
Foot Rest	Std	Std
Ventrac Mount System	Std	Std
ROPS	Std / Fold Down Opt.	Std / Fold Down Opt.
Weight (appx)	1560	1580

* S.D.L.A.- Speed, Direction, Lift, AUX. Control / single hand operation

Specifications Subject to Change Without Notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com