



4100 Specification Comparison **4100**

Gas, Air Cooled

Model 4131A	
Stock Code	3.95112
Power Unit:	
Engine Manufacturer	Briggs & Stratton
Engine Model	543477-0144
Horsepower	31
Configuration	2-cylinder
Cooling	Air-Cooled
CARB Compliant Engine	Yes
EPA Compliant Engine	Yes
Air Filtration	Donaldson 2-stage
Spin-on Oil Filter	Yes
Electrical System	50 amp
Starter	Electric
Battery Capacity	12V/450CCA
Transmission:	
Drive	AWD
High/Low Shift from Seat	Std
Transmission	Hydrostatic
Forward/Reverse Speed, High Range	0-10 MPH (0-16.1 KPH) Infinitely variable
Forward/Reverse Speed, Low Range	0-5.2 MPH (0-8.4 KPH) Infinitely variable
Transaxles	Peerless 2600 2-speed
Brakes	Hydro-Dynamic
Spin-on Oil Filter-suction	25 microns
Spin-on Oil Filter-pressure	10 microns
Controls/Instrumentation:	
Steering	Power
PTO Clutch	Electric w/Brake
Throttle Control/Choke	Std w/Manual Choke
Operator Control *	S.D.L.A. / Std *
Speed Control	Easy Shift
Gauges: Hour/Tach	Std
Park Brake/Emergency	16 in ² brake surface (103 cm ²)

Model 4131A	
Other Features:	
Center Articulated Tractor	Yes
Turning Radius	43 Inches (109 cm)
Drive Tires	22 x 12-8 HD Field Trax (56x31x20 cm)
Optional Tires	21 x 11-8 Bar (53x28x20 cm)
	22 X 11-10 Turf Master (56x28x25 cm)
Seat-Spring Ride	Std
Front Fenders	Optional
Headlights, Halogen	Std
Fuel Tank Capacity	7.25 gal. (27 L)
Visual Fuel Gauge Slot	Std
Counter Weights	Optional
Weight Transfer System	Optional
Racor Fuel Water Separator	Optional
Foot Rest	Optional
Ventrac Mount System	Std
Fold Down Roll Bar	Optional
Weight (appx)	1290 lbs (585 kgs)

* S.D.L.A.- Speed, Direction, Lift, AUX. Control / single hand operation
Specifications Subject to Change Without Notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC (836.8722)
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com

